

DAIHAN-brand® 1mg~110g High-performance Moisture Analyzer, "WBA-110M", 0.00 ~ 100.00 %, 40~199 °C NEW
 with 100g Cali. Weight, Back Light LCD, Counting Function, 3 × displays of %(g) / °C / Time, & Ext-CAL program



Included 100g Calibration Weight

2-Year Warranty

1mg~110g High-performance Moisture Analyzer "WBA-110M"

- with Certificate & Traceability :
 Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Included 100g Calibration Weight
- Halogen Light Heating
- Temperature and Time can be Set
- The Percentage of Dry Residual
- Store Historical Setting
- The Percentage of moisture Content
- 3 × Display after Drying : Humidity(%) - Reduce Weight of Liquid
 Dry Mass(%) - Weight of Solid
 ATRO(%) - 100 ~ 999%
- Stainless steel Chamber
- External Calibration
- Back Light LCD
- CE Certified

- * Digital Function, and AC 220V, 50/60Hz Operated
- * Operating Temperature 5.0~35°C
- * Default and Auto Lock Present Working Mode
- * Built in RS232C & USB port for Printer
- * Loadcell Sensor
- * Included 10ea Sample Plates

Specification

Spec.	Model	"WBA-110M"
Weighing Range. g		0.001 ~ 110 g
Weighing Plate. mm		φ 90 mm
Read-Out [d]. g		0.01 mg
Reproducibility. g		0.1 mg
Permissible Temperature		5.0~35°C
Heat Source / Temp. Sensor		Halogen Lamp / PT100 Sensor
Temp. Range / Resolution		40 ~ 199 °C / 1 °C
Moisture Range / Read ability		0.00 ~ 100% / 0.01%
Dry Residual		Range : 0.00 ~ 100.00%, Read ability : 0.01%
ATRO		100 ~ 999%, 0 ~ 999%
Timer / Auto-stop		1 ~ 99min(Resolution : 1Sec.) / Auto-stop 0.1~9.9% within 1min.
Number of Storage		15
Calibration		External Calibration, Included 100g Calibration Weight
Display		Digital LCD with Back-Light Function
Power Consumption		400 W
Dimension & Net Weight		180 × 200 × h380 mm / 5.8 kg
Packing Size & Gross Weight		290 × 305 × h440 mm / 6.4 kg
Power Supply & Cord Plug		AC 220V, 50 / 60Hz

Ordering Information

DH.WBA110M Digital Moisture Analyzer, 1mg~110g, "WBA-110M"
 40 ~ 199 °C, 0.00 ~ 100%, AC 220V, 50/60Hz

Optional Sample Plates

DH.WBA0005 (1) Sample Plates, φ90 mm, 10ea, "WBA-0005"

Optional Thermal Printer

DH.WBA0083 (2) Thermal Printer, Paper Roll, "WBA-083"
 Included Cable Module, 1 × Paper Roll

DH.WBA0084 Thermal Paper Package, 5 × Paper Roll, "WBA-0084" for "WBA-083"

DH.WBA0770 (3) Thermal Printer, Label Paper Roll, "WBA-770"
 Included Cable Module, 1 × Label Paper Roll

DH.WBA0771 Thermal Label Paper Package, 5 × Label Paper Roll, "WBA-0771" for "WBA-770"



(1) 10ea Sample Plates(Included)



(2) RS-232C Thermal Printer, Paper "WBA-083"



(3) RS-232C Thermal Printer, Label "WBA-770"