

工業用連接器



台灣大昌華嘉提供LAPP - EPIC®工業用連接器

提供您與其他電纜產品安全可靠的搭配，無論是電源供應或訊號傳輸皆能夠讓您意。產品範圍從方型或圓型連接器以及相關零配件，都能夠一應俱全滿足您多樣化的求。

方形連接器

EPIC® H-A 3 Kits Thermoplastic	83
EPIC® H-A 3 Kits Metal	84
EPIC® H-A 4 Kits Thermoplastic	85
EPIC® H-A 4 Kits Metal	86
EPIC® H-A 10 Kits	87
EPIC® H-A 16 Kits	88
EPIC® H-BE 6 Kits	89
EPIC® H-BE 10 Kits	90
EPIC® H-BE 16 Kits	91
EPIC® H-BE 24 Kits	92
EPIC® H-BS 6 Kits	93
EPIC® H-D 40 Kits	94
EPIC® H-D 64 Kits	95

H-D 1.6 端子及手工具

EPIC® H-D 1.6 machined contacts / Tools	96
EPIC® H-D 1.6 stamped contacts / Tools	97

H-BE 2.5 端子及手工具

EPIC® H-BE 2.5 machined contacts / Tools	98
--	----

MC 2.5 端子及手工具

EPIC® MC 2.5 machined contacts / Tools	99
EPIC® MC 2.5 stamped contacts / Tools	100

MC 3.6 端子及手工具

EPIC® MC 3.6 machined contacts / Tools	101
--	-----

M23 圓形連接器

EPIC® M23 Kits 12pole	102
EPIC® M23 Kits 17pole	103

M23 端子及手工具

EPIC® M23 Contacts male	104
EPIC® M23 Contacts female	104
EPIC® M23 Tools	104
EPIC® M23 Accessories	104

LS1 圓形連接器

EPIC® LS1 Kits 6Pole	105
----------------------	-----

LS1 圓形連接器

EPIC® LS1 Kits 8Pole	106
----------------------	-----

LS1 端子及手工具

EPIC® LS1 Contacts male	107
EPIC® LS1 Contacts female	107
EPIC® LS1 Tools	107
EPIC® LS1 Accessories	107

EPIC® H-A 3 Kits Thermoplastic



料號	規格	包裝數量	
75009601	EPIC KIT H-A 3 SS TG M20	1	



料號	規格	包裝數量	
75009603	EPIC KIT H-A 3 SS TS M20	1	



料號	規格	包裝數量	
75009605	EPIC KIT H-A 3 BS AG	1	



料號	規格	包裝數量	
75009607	EPIC KIT H-A 3 BS AGS	1	



料號	規格	包裝數量	
75009609	EPIC KIT H-A 3 BS AGS M20	1	



料號	規格	包裝數量	
75009611	EPIC KIT H-A 3 BS TGB M20	1	



■ 技術參數



額定電壓：
IEC : 400 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 23 A
UL : 10 A
CSA : 10 A

接點數 : 3 + PE

EPIC® H-A 3 Kits Metal



料號	規格	包裝數量	
75009602	EPIC KIT H-A 3 SS MTG M20	1	



料號	規格	包裝數量	
75009604	EPIC KIT H-A 3 SS MTS M20	1	



料號	規格	包裝數量	
75009606	EPIC KIT H-A 3 BS MAG	1	



料號	規格	包裝數量	
75009608	EPIC KIT H-A 3 BS MAGS	1	



料號	規格	包裝數量	
75009610	EPIC KIT H-A 3 BS MAGS M20	1	



料號	規格	包裝數量	
75009610	EPIC KIT H-A 3 BS MAGB M20	1	



■ 技術參數



額定電壓：
IEC : 400 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 23 A
UL : 10 A
CSA : 10 A

接點數 : 3 + PE

EPIC® H-A 4 Kits Thermoplastic



料號	規格	包裝數量	
75009613	EPIC KIT H-A 4 SS TG M20	1	



料號	規格	包裝數量	
75009615	EPIC KIT H-A 4 SS TS M20	1	



料號	規格	包裝數量	
75009617	EPIC KIT H-A 4 BS AG	1	



料號	規格	包裝數量	
75009619	EPIC KIT H-A 4 BS AGS	1	



料號	規格	包裝數量	
75009621	EPIC KIT H-A 4 BS AGS M20	1	



料號	規格	包裝數量	
75009623	EPIC KIT H-A 4 BS TGB M20	1	



■ 技術參數



額定電壓：
IEC : 400 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 23 A
UL : 10 A
CSA : 10 A

接點數：4 + PE

EPIC® H-A 4 Kits Metal



料號	規格	包裝數量	
75009614	EPIC KIT H-A 4 SS MTG M20	1	



料號	規格	包裝數量	
75009616	EPIC KIT H-A 4 SS MTS M20	1	



料號	規格	包裝數量	
75009618	EPIC KIT H-A 4 BS MAG	1	



料號	規格	包裝數量	
75009620	EPIC KIT H-A 4 BS MAGS	1	



料號	規格	包裝數量	
75009622	EPIC KIT H-A 4 BS MAGS M20	1	



料號	規格	包裝數量	
75009624	EPIC KIT H-A 4 BS TGB M20	1	



技術參數



額定電壓：
IEC : 400 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 23 A
UL : 10 A
CSA : 10 A

接點數 : 4 + PE

EPIC® H-A 10 Kits



料號	規格	包裝數量	
75009625	EPIC KIT H-A 10 SS TG M20	1	



料號	規格	包裝數量	
75009626	EPIC KIT H-A 10 SS TS M20	1	



料號	規格	包裝數量	
75009627	EPIC KIT H-A 10 BS AG	1	



料號	規格	包裝數量	
75009628	EPIC KIT H-A 10 BS SGR-LB M20	1	



料號	規格	包裝數量	
75009629	EPIC KIT H-A 10 BS TBF-LB M20	1	



■ 技術參數



額定電壓：
IEC : 250 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 14 A
CSA : 16 A

接點數 : 10 + PE

EPIC® H-A 16 Kits



料號	規格	包裝數量	
75009630	EPIC KIT H-A 16 SS TG M20	1	



料號	規格	包裝數量	
75009631	EPIC KIT H-A 16 SS TS M20	1	



料號	規格	包裝數量	
75009632	EPIC KIT H-A 16 BS AG	1	



料號	規格	包裝數量	
75009633	EPIC KIT H-A 16 BS SGR-LB M20	1	



料號	規格	包裝數量	
75009634	EPIC KIT H-A 16 BS TBF-LB M20	1	



技術參數



額定電壓：
IEC : 250 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 14 A
CSA : 16 A

接點數 : 16 + PE

EPIC® H-BE 6 Kits



料號	規格	包裝數量	
75009635	EPIC KIT H-BE 6 SS TG M20	1	



料號	規格	包裝數量	
75009636	EPIC KIT H-BE 6 SS TS M20	1	



料號	規格	包裝數量	
75009637	EPIC KIT H-BE 6 BS AG-LB	1	



料號	規格	包裝數量	
75009638	EPIC KIT H-BE 6 BS SGR-LB M20	1	



料號	規格	包裝數量	
75009639	EPIC KIT H-BE 6 BS TBF-LB M20	1	



■ 技術參數



額定電壓：
IEC : 500 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 16 A
CSA : 16 A

接點數 : 6 + PE

EPIC® H-BE 10 Kits



料號	規格	包裝數量	
75009640	EPIC KIT H-BE 10 SS TG M25	1	



料號	規格	包裝數量	
75009641	EPIC KIT H-BE 10 SS TS M25	1	



料號	規格	包裝數量	
75009642	EPIC KIT H-BE 10 BS AG	1	



料號	規格	包裝數量	
75009643	EPIC KIT H-BE 10 BS SGR M25	1	



料號	規格	包裝數量	
75009644	EPIC KIT H-BE 10 BS TBF M25	1	



技術參數



額定電壓：
IEC : 500 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 16 A
CSA : 16 A

接點數 : 10 + PE

EPIC® H-BE 16 Kits



料號	規格	包裝數量	
75009645	EPIC KIT H-BE 16 SS TG M25	1	



料號	規格	包裝數量	
75009646	EPIC KIT H-BE 16 SS TS M25	1	



料號	規格	包裝數量	
75009647	EPIC KIT H-BE 16 BS AG	1	



料號	規格	包裝數量	
75009648	EPIC KIT H-BE 16 BS SGR M25	1	



料號	規格	包裝數量	
75009649	EPIC KIT H-BE 16 BS TBF M25	1	



■ 技術參數



額定電壓：
IEC : 500 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 16 A
CSA : 16 A

接點數 : 16 + PE

EPIC® H-BE 24 Kits



料號	規格	包裝數量	
75009650	EPIC KIT H-BE 24 SS TG M25	1	



料號	規格	包裝數量	
75009651	EPIC KIT H-BE 24 SS TS M25	1	



料號	規格	包裝數量	
75009652	EPIC KIT H-BE 24 BS AG	1	



料號	規格	包裝數量	
75009653	EPIC KIT H-BE 24 BS SGR M25	1	



料號	規格	包裝數量	
75009654	EPIC KIT H-BE 24 BS TBF M25	1	



技術參數



額定電壓：
IEC : 500 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 16 A
UL : 16 A
CSA : 16 A

接點數 : 24 + PE

EPIC® H-BS 6 Kits



料號	規格	包裝數量	
75009655	EPIC KIT H-BE 6 SS TG M25	1	



料號	規格	包裝數量	
75009656	EPIC KIT H-BS 6 SS TS M25	1	



料號	規格	包裝數量	
75009657	EPIC KIT H-BE 6 BS AG-LB	1	



料號	規格	包裝數量	
75009658	EPIC KIT H-BS 6 BS SGR M25	1	



料號	規格	包裝數量	
75009659	EPIC KIT H-BS 6 BS TBF-LB M20	1	



■ 技術參數



額定電壓：
IEC : 400 V
UL : 600 V
CSA : 600 V



額定電流：
IEC : 35 A
UL : 35 A
CSA : 36 A

接點數 : 6 + PE

EPIC® H-D 40 Kits



料號	規格	包裝數量	
75009660	EPIC KIT H-D 40 SCM TG M32	1	



料號	規格	包裝數量	
75009661	EPIC KIT H-D 40 SCM TS M32	1	



料號	規格	包裝數量	
75009662	EPIC KIT H-D 40 BCM AG	1	



料號	規格	包裝數量	
75009663	EPIC KIT H-D 40 BCM SGR M25	1	



料號	規格	包裝數量	
75009664	EPIC KIT H-D 40 BCM SGR M25	1	



技術參數



額定電壓：
IEC : 250 V
UL : 250 V



額定電流：
IEC : 10 A
UL : 10 A

接點數 : 40 + PE

EPIC® H-D 64 Kits



料號	規格	包裝數量	
75009665	EPIC KIT H-D 64 SCM TG M32	1	



料號	規格	包裝數量	
75009666	EPIC KIT H-D 64 SCM TS M32	1	



料號	規格	包裝數量	
75009667	EPIC KIT H-D 64 BCM AG	1	



料號	規格	包裝數量	
75009668	EPIC KIT H-D 64 BCM SGRL M25	1	



料號	規格	包裝數量	
75009669	EPIC KIT H-D 64 BCM TBF M32	1	



■ 技術參數



額定電壓：
IEC : 250 V
UL : 250 V



額定電流：
IEC : 10 A
UL : 10 A

接點數 :64+ PE

EPIC® H-D 1.6 machined contacts / Tools



料號	品名	規格	適用導體 mm ²	材質	剝線長度 mm	包裝數量
Contacts						
13162000	H-D 1.6 machined	male	0.14 - 0.37	Ag	8.0	100
13163000	H-D 1.6 machined	female	0.14 - 0.37	Ag	8.0	100
13162100	H-D 1.6 machined	male	0.50	Ag	8.0	100
13163100	H-D 1.6 machined	female	0.50	Ag	8.0	100
13162200	H-D 1.6 machined	male	0.75 - 1.00	Ag	8.0	100
13163200	H-D 1.6 machined	female	0.75 - 1.00	Ag	8.0	100
13162300	H-D 1.6 machined	male	1.50	Ag	8.0	100
13163300	H-D 1.6 machined	female	1.50	Ag	8.0	100
13162400	H-D 1.6 machined	male	2.50	Ag	5.8	100
13163400	H-D 1.6 machined	female	2.50	Ag	5.8	100
13162500	H-D 1.6 machined	male	0.14 - 0.37	Au	8.0	100
13163500	H-D 1.6 machined	female	0.14 - 0.37	Au	8.0	100
13162600	H-D 1.6 machined	male	0.50	Au	8.0	100
13163600	H-D 1.6 machined	female	0.50	Au	8.0	100
13162700	H-D 1.6 machined	male	0.75 - 1.00	Au	8.0	100
13163700	H-D 1.6 machined	female	0.75 - 1.00	Au	8.0	100
13162800	H-D 1.6 machined	male	1.50	Au	8.0	100
13163800	H-D 1.6 machined	female	1.50	Au	8.0	100
13162900	H-D 1.6 machined	male	2.50	Au	5.8	100
13163900	H-D 1.6 machined	female	2.50	Au	5.8	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147100	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE 2.5 machined, MC 2.5 machined	1
11147200	Locator	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE 2.5 machined, MC 2.5 machined, MC 2.5 stamped	1
11161000	Removal tool		For contacts: H-D 1.6 machined, H-D 1.6 stamped	1

EPIC® H-D 1.6 stamped contacts / Tools



料號	品名	規格	適用導體 mm ²	材質	剝線長度 mm	包裝數量
Contacts						
11241100	H-D 1.6 stamped	male	0.14 - 0.50	Ag	2.5 + 0.5	100
11231100	H-D 1.6 stamped	female	0.14 - 0.50	Ag	2.5 + 0.5	100
11221000	H-D 1.6 stamped	male	0.50 - 1.50	Ag	3.5 + 0.5	100
11236100	H-D 1.6 stamped	female	0.50 - 1.50	Ag	3.5 + 0.5	100
11223500	H-D 1.6 stamped	male	1.50 - 2.50	Ag	3.5 + 0.5	100
11228500	H-D 1.6 stamped	female	1.50 - 2.50	Ag	3.5 + 0.5	100
11243100	H-D 1.6 stamped	male	0.14 - 0.50	Au	2.5 + 0.5	100
11233100	H-D 1.6 stamped	female	0.14 - 0.50	Au	2.5 + 0.5	100
11221300	H-D 1.6 stamped	male	0.50 - 1.50	Au	3.5 + 0.5	100
11238100	H-D 1.6 stamped	female	0.50 - 1.50	Au	3.5 + 0.5	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147170	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 stamped (0.14 - 0.5 mm ²)	1
11147180	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 stamped (0.5 - 1.5 mm ²), MC 2.5 stamped (0.5 - 1.5 mm ²)	1
11147190	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 stamped (1.5 - 2.5 mm ²), MC 2.5 stamped (1.5 - 2.5 mm ²)	1
11147300	Locator		For contacts: H-D 1.6 machined, H-D 1.6 stamped	1
11161000	Removal tool		For contacts: H-D 1.6 machined, H-D 1.6 stamped	1

EPIC® H-BE 2.5 machined contacts / Tools



料號	品名	規格	適用導體 mm ²	Cross-section ratio	材質	剝線長度 mm	包裝數量
Contacts							
11190000	H-BE 2.5 machined	male	0.50		Ag	7.4	100
11195000	H-BE 2.5 machined	female	0.50		Ag	7.3	100
11190100	H-BE 2.5 machined	male	0.75 - 1.00	1.0	Ag	7.4	100
11195100	H-BE 2.5 machined	female	0.75 - 1.00	1.0	Ag	7.3	100
11190200	H-BE 2.5 machined	male	1.50	2.0	Ag	7.4	100
11195200	H-BE 2.5 machined	female	1.50	2.0	Ag	7.3	100
11190300	H-BE 2.5 machined	male	2.50	3.0	Ag	7.4	100
11195300	H-BE 2.5 machined	female	2.50	3.0	Ag	7.3	100
11190400	H-BE 2.5 machined	male	4.00		Ag	7.4	100
11195400	H-BE 2.5 machined	female	4.00		Ag	7.3	100
11192000	H-BE 2.5 machined	male	0.50		Au	7.4	100
11197000	H-BE 2.5 machined	female	0.50		Au	7.3	100
11192100	H-BE 2.5 machined	male	0.75 - 1.00	1.0	Au	7.4	100
11197100	H-BE 2.5 machined	female	0.75 - 1.00	1.0	Au	7.3	100
11192200	H-BE 2.5 machined	male	1.50	2.0	Au	7.4	100
11197200	H-BE 2.5 machined	female	1.50	2.0	Au	7.3	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147100	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE 2.5 machined, MC 2.5 machined	1
11147200	Locator	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE machined, MC 2.5 machined, MC 2.5 stamped	1
11182500	Removal tool		For contacts: H-BE 2.5 machined	1

EPIC® MC 2.5 machined contacts / Tools



料號	品名	規格	適用導體 mm ²	Cross-section ratio	材質	剝線長度 mm	包裝數量
Contacts							
1121300C	MC 2.5 machined	male	0.50		Ag	7.8	100
1121800C	MC 2.5 machined	female	0.50		Ag	7.8	100
1121310C	MC 2.5 machined	male	1.00	1.0	Ag	7.8	100
1121810C	MC 2.5 machined	female	1.00	1.0	Ag	7.8	100
1121320C	MC 2.5 machined	male	1.50	2.0	Ag	7.8	100
1121820C	MC 2.5 machined	female	1.50	2.0	Ag	7.8	100
1121330C	MC 2.5 machined	male	2.50	3.0	Ag	7.8	100
1121830C	MC 2.5 machined	female	2.50	3.0	Ag	7.8	100
1121340C	MC 2.5 machined	male	4.00		Ag	7.8	100
1121840C	MC 2.5 machined	female	4.00		Ag	7.8	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147100	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE 2.5 machined, MC 2.5 machined	1
11147200	Locator	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 machined, H-BE machined, MC 2.5 machined, MC 2.5 stamped	1
11171000	Removal tool		For contacts: MC 2.5 machined	1

EPIC® MC 2.5 stamped contacts / Tools



料號	品名	規格	適用導體 mm ²	材質	剝線長度 mm	包裝數量
Contacts						
11201000	MC 2.5 stamped	male	0.50 - 1.50	Ag	3.5 + 0.5	100
11205000	MC 2.5 stamped	female	0.50 - 1.50	Ag	3.5 + 0.5	100
11202000	MC 2.5 stamped	male	1.50 - 2.50	Ag	3.5 + 0.5	100
11206000	MC 2.5 stamped	female	1.50 - 2.50	Ag	3.5 + 0.5	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147180	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 stamped (0.5 - 1.5 mm ²), MC 2.5 stamped (0.5 - 1.5 mm ²)	1
11147190	Crimping dies	For crimping tools 11147000, 11147001	For contacts: H-D 1.6 stamped (1.5 - 2.5 mm ²), MC 2.5 stamped (1.5 - 2.5 mm ²)	1
11147300	Locator		For contacts: H-D 1.6 machined, H-D 1.6 stamped	1
11160000	Removal tool		For contacts: MC 2.5 stamped	1

EPIC® MC 3.6 machined contacts / Tools



料號	品名	規格	適用導體 mm ²	材質	剝線長度 mm	包裝數量
Contacts						
1121070C	MC 3.6 machined	male	1.50	Ag	10.0	100
1121570C	MC 3.6 machined	female	1.50	Ag	10.0	100
1121060C	MC 3.6 machined	male	2.50	Ag	10.0	100
1121560C	MC 3.6 machined	female	2.50	Ag	10.0	100
1121000C	MC 3.6 machined	male	4.00	Ag	10.0	100
1121500C	MC 3.6 machined	female	4.00	Ag	10.0	100
1121010C	MC 3.6 machined	male	6.00	Ag	10.0	100
1121510C	MC 3.6 machined	female	6.00	Ag	10.0	100
1121020C	MC 3.6 machined	male	10.00	Ag	10.0	100
1121520C	MC 3.6 machined	female	10.00	Ag	10.0	100

料號	品名	規格	備註	包裝數量
Tools				
11147000	Crimping tool	In tool case	Without crimping dies, without locator	1
11147001	Crimping machine	Pneumatic, 5-10 bar	Without crimping dies, without locator	1
11147110	Crimping dies	For crimping tools 11147000, 11147001	For contacts: MC 3.6 machined (1.5 - 2.5 mm ²)	1
11147120	Crimping dies	For crimping tools 11147000, 11147001	For contacts: MC 3.6 machined (4.0 - 10 mm ²)	1
11147210	Locator	For crimping tools 11147000, 11147001	For contacts: MC 3.6 machined (1.5 - 2.5 mm ²)	1
11171100	Removal tool		For contacts: MC 3.6 machined (1.5 - 2.5 mm ²)	1

EPIC® M23 Kits 12pole



料號	規格	包裝數量	
75009702	EPIC KIT M32 D6 12-POL FEMALE	1	



料號	規格	包裝數量	
75009703	EPIC KIT M23 A1 12-POL MALE	1	



料號	規格	包裝數量	
75009704	EPIC KIT M23 A3 12-POL MALE	1	



料號	規格	包裝數量	
75009705	EPIC KIT M23 A6 12-POL MALE	1	



■ 技術參數



額定電壓：
100 V (1mm)



額定電流：
7 A (1mm)

接點數：12

EPIC® M23 Kits 17pole



料號	規格	包裝數量	
75009706	EPIC KIT M23 D6 17-POL FEMALE	1	



料號	規格	包裝數量	
75009707	EPIC KIT M23 A1 17-POL MALE	1	



料號	規格	包裝數量	
75009708	EPIC KIT M23 A3 17-POL MALE	1	



料號	規格	包裝數量	
75009709	EPIC KIT M23 A6 17-POL MALE	1	



■ 技術參數	
	額定電壓： 50 V (1mm)
	額定電流： 7 A (1mm)
接點數：17	

EPIC® M23 Contacts male



EPIC® M23 Contacts female



料號	品名	規格	適用範圍	包裝數量
Contacts male				
72400001	EPIC® M23 SCEM 1 mm AU 0.14 - 1.0 (10)	1 mm male crimp	M23 inserts (not D-Sub)	10
72400000	EPIC® M23 SCEM 1 mm AU 0.14 - 1.0 (100)	1 mm male crimp	M23 inserts (not D-Sub)	100
72402001	EPIC® M23 SLEM 1 mm AU 1.0 (10)	1 mm male solder	M23 inserts (not D-Sub)	10
72402000	EPIC® M23 SLEM 1 mm AU 1.0 (100)	1 mm male solder	M23 inserts (not D-Sub)	100
72401000	EPIC® M23 SCEM 2 mm AU 1.0 - 2.5 (100)	2 mm male crimp	M23 inserts (not D-Sub)	100
72403100	EPIC® M23 SLEM 2 mm AU (10)	2 mm male solder	M23 inserts (not D-Sub)	10
72403000	EPIC® M23 SLEM 2 mm AU (100)	2 mm male solder	M23 inserts (not D-Sub)	100
Contacts female				
74020601	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female slot 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6	10
74200600	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female slot 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6	100
72402601	EPIC® M23 BLEMS 1 mm 1.0 AU (10)	1 mm female slot solder	M23 inserts (not D-Sub)	10
72402600	EPIC® M23 BLEMS 1 mm 1.0 AU (100)	1 mm female slot solder	M23 inserts (not D-Sub)	100
72401601	EPIC® M23 BCEMS 2 mm AU 1.0 - 2.5 (10)	2 mm female crimp	M23 inserts (not D-Sub)	10
72401600	EPIC® M23 BCEMS 2 mm AU 1.0 - 2.5 (100)	2 mm female crimp	M23 inserts (not D-Sub)	100
72404100	EPIC® M23 BLEMS 2 mm AU 1.0 - 2.5 (10)	2 mm female solder	M23 inserts (not D-Sub)	10
72404000	EPIC® M23 BLEMS 2 mm AU 1.0 - 2.5 (100)	2 mm female solder	M23 inserts (not D-Sub)	100
74034501	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female hyper boloid 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6	10
74034500	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female hyper boloid 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6	100

EPIC® M23 Tools



料號	品名	備註	包裝數量
Tools			
11148000	Crimping tool	in tool case, without locator	1
11148001	Crimping tool digital	in tool case, without locator	1
11148002	Crimping machine	Pneumatic for 5-10 bar, Locator not included	1
11148300	Locator for EPIC® CIRCON	-	1
44420078	M23 removal tool for inserts	For type A, B, G, O	1

EPIC® M23 Accessories



料號	品名	備註	包裝數量
Accessories			
75018310	LS1 A, G, F Protection cap, plastic cord with cable lug	Metal cap for A1, F6, F7, G5	20
75007810	M23-LS1 A,B,F,G Protection cap	Plastic cap for A1, F6	20
75007710	M23-LS1 D Protection cap	Plastic cap for D6, A6	20
75018010	M23 A, B, F, G Protection cap, plastic cord with cable lug	Metal cap for A1, F6	20
75018110	M23 A Protection cap, plastic cord with grommet	Metal cap for A1	20
55001312	SILVYN ADAPTER M23/M20x1,5	For clamping range 8,5 - 11 mm and 10,5 - 15,5 mm	1

EPIC® LS1 Kits 6pole



料號	規格	包裝數量	
75009690	EPIC KIT LS1 D6 6-POL FEMALE	1	



料號	規格	包裝數量	
75009691	EPIC KIT LS1 A1 6-POL MALE	1	



料號	規格	包裝數量	
75009692	EPIC KIT LS1 A3 6-POL MALE	1	



料號	規格	包裝數量	
75009693	EPIC KIT LS1 F6 6-POL MALE	1	



■ 技術參數



額定電壓：
630 V (2mm)




額定電流：
26 A (6mm)

接點數：5+PE

EPIC® LS1 Kits 8pole




料號	規格	包裝數量	
75009694	EPIC KIT LS1 D6 8-POL FEMALE	1	




料號	規格	包裝數量	
75009695	EPIC KIT LS1 A1 8-POL MALE	1	



料號	規格	包裝數量	
75009696	EPIC KIT LS1 A3 8-POL MALE	1	



料號	規格	包裝數量	
75009697	EPIC KIT LS1 F3 8-POL MALE	1	



■ 技術參數



額定電壓：
630 V (2mm)
250 V (1mm)



額定電流：
26 A (6mm)
7 A (1mm)

接點數：5+PE+4

EPIC® LS1 Contacts male



EPIC® LS1 Contacts female



料號	品名	規格	包裝數量
Contacts male			
74033001	LS1 A SCEM 1 mm AU 0.14 - 1.0 (10)		10
74033000	LS1 A SCEM 1 mm AU 0.14 - 1.0 (100)		100
74034001	LS1 F SCEM 1 mm AU 0.14 - 1.0 (10)		10
74034000	LS1 F SCEM 1 mm AU 0.14 - 1.0 (100)		100
74033101	LS1 A SCEM 2 mm AU 0.5 - 2.5 (10)		10
74033100	LS1 A SCEM 2 mm AU 0.5 - 2.5 (100)		100
74034101	LS1 F SCEM 2 mm AU 0.5 - 2.5 (10)		10
74034100	LS1 F SCEM 2 mm AU 0.5 - 2.5 (100)		100
44420103	LS1 F SCEM 2 mm AU 4.0 (100)		100
Contacts female			
74020601	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female slot 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6
74200600	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female slot 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6
74034501	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female hyper boloid 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6
74034500	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female hyper boloid 0.14-1.0mm ²	M23 inserts (not D-Sub), LS1 D6, A6
74034601	LS1 D BCEMD 2 mm AU 0.5 - 2.5 (10)	2 mm female hyper boloid 0.5-2.5mm ²	LS1 D6, A6
74034600	LS1 D BCEMD 2 mm AU 0.5 - 2.5 (100)	2 mm female hyper boloid 0.5-2.5mm ²	LS1 D6, A6
44420104	LS1 D BCEMD 2 mm AU 4.0 (10)	2mm female hyper boloid 4mm ²	LS1 D6
44420105	LS1 D BCEMD 2 mm AU 4.0 (100)	2mm female hyper boloid 4mm ²	LS1 D6
44429001	EPIC CIRCON BCBG 2MM 1.0-2.5 (3000) RE	2 mm female crimp	LS1 D6, A6

EPIC® LS1 Tools



料號	品名	規格	包裝數量
11148000	Crimping tool	in tool case, without locator	1
11148001	Crimping tool digital	in tool case, without locator	1
11148002	Crimping machine	Pneumatic for 5-10 bar, Locator not included	1
11148300	Locator for EPIC® CIRCON	-	1
75017400	LS1 Removal tool for 1 mm contacts	For type A1, G5	1
75017500	LS1 Removal tool for 2 mm contacts	For type A1, G5	1

EPIC® LS1 Accessories



料號	品名	規格	包裝數量
75018310	LS1 A, G, F Protection cap, plastic cord with cable lug	Metal cap for A1, F6, F7, G5	20
75007810	M23-LS1 A,B,F,G Protection cap	Plastic cap for A1, F6	20
75007710	M23-LS1 D Protection cap	Plastic cap for D6, A6	20
75018010	M23 A, B, F, G Protection cap, plastic cord with cable lug	Metal cap for A1, F6	20
75018110	M23 A Protection cap, plastic cord with grommet	Metal cap for A1	20
55001310	SILVYN Adapter LS1/M25x1,5	For clamping range 8,5 - 11 mm and 10,5 - 15,5 mm	1